


**WEEM** ABRASIVES

威鸣研磨



**涂附磨具产品目录 2018**  
PROFESSIONAL COATED ABRASIVE  
PRODUCT CATALOGUE 2018



[www.威鸣.com](http://www.威鸣.com)

[联系我们](#)



[www.weem-abrasives.com](http://www.weem-abrasives.com)

[Contact Us](#)

## 目录 Content

关于我们 COMPANY PROFILE	1
技术说明 TECHNICAL INFORMATION	4
砂纸产品 PAPER BACKING ABRASIVE	5
砂布产品 CLOTH BACKING ABRASIVE	7
多方向砂布产品 SEGMENTED BELT READY CLOTH BACKING ABRASIVE	11
金属材料表面处理 ABRASIVE FOR METAL SURFACE	13
硬金属打磨 ZIRCONIA ALUMINA FOR METAL	14
钢纸基产品 VULCANIZED FIBER	15
配件 ACCESSORIES	16



**设备**

源于对品质的追求威鸣研磨在设备投入上，特别是重型砂纸、砂布制造线中关乎产品质量的头胶和植砂工序引进国际一流的意大利砂纸、砂布设备制造商G.T. Engineering的设备，使产品品质得到保证。还投入过百万的资金引进了生产质量在线监测系统。

**Equipment**

The leading coat abrasive production line and technology from G. T. Engineering Italy ensure the best quality of sanding jumbo rolls. Cloth backing process line and German basic technology is also in use to enhance the stability of our cloth backing products.



**关于我们**

威鸣研磨是一家涂附磨具研发、生产及服务供应商。威鸣研磨于1994年创立，并拥有及经营“WEEM®”品牌产品。涵盖从事砂布、砂纸的大卷、砂带以及砂碟等磨具产品的生产及销售。威鸣研磨是国内最早引进进口砂带转接设备，用涂附磨具大卷在国内加工制作高端工业宽砂带、超宽砂带的企业；通过自己技术能力先后研发针对木工打磨，通用打磨，金属打磨各类涂附磨具产品。

威鸣研磨依靠自身的努力和发展，从下游加工技术升级至上游生产的一家自强不息的民营企业。威鸣研磨起源广东，并在全国板材行业最发达的地区深耕。以优质的服务，过硬的技术强势进驻国内大型板材企业主要的供应商。

**About Us**

WEEM Abrasives is a professional coated abrasives manufacturer. We manufacture coated abrasives: jumbo rolls, belts, rolls, discs, sheets and even customize abrasives for special needs for use in sanding, grinding, blending, finishing and polishing applications. The combination of several minerals, resin systems and backings results in a wide variety of products to meet requirements for use on most surfaces. Available as: Aluminium oxide, Silicon carbide, Zirconia, etc.

We also provide in field adviser, who have rich experience in sanding, to help client deal with problems on sanding, or getting better surface quality.

**原材料**

源于威鸣研磨成长经历，深知原材料品质对于最终产品的影响巨大。秉承高品质生产工艺技术要求，严格筛选供应商，采用高品质且稳定的国内、外原材料供应商。

**Raw Materials**

Our careful choice of premium materials, leading manufacturing equipment and sophisticated production technologies enable us to manufacture top quality coated abrasive.




**质量控制**

为保证高品质质量控制，投入采购了一系列的研发设备，检验设备。并重视引进国内外先进涂附研磨设备、技术及管理。并于2017年通过ISO9001质量管理体系认证。

**Quality Control**

We keep quality in mind, and have ISO 9001 certificated. Other Quality Control equipments, such as online QC detector, are also in place for quality guarantee.



## 技术说明 Technical Information

### 转换加工

国内最早引进的意大利Biko Meccanics公司的整套转换设备。并采用德国标准化的砂带拨接技术转换砂带，是国内最早转换超宽幅研磨砂带的供应商之一。



### Converting

Full set of Biko Meccanics jointing machines, Sheldehl tapes and Buyer glue are used to provide best belt joint. And produce high quality wide belts and segmented belts, Up to 3300mm width by 4000mm length.




#### 产品类 Product type

涂附磨具大卷 / 砂卷 Sanding jumbo roll Sanding roll	
圆盘磨片 Sanding disc	
窄带 / 长带 Narrow belt Long belt	
宽砂带 / 超宽带 Wide belt Segmented belt	

#### 砂带接头型 Joint shape for belt

直线对接 Line shape	
默认砂带对接方式 Available for all belts	
S型对接 S-line shape	
超宽带除外 Non-available for segmented belt	

#### 砂带接头方式 Joint type for belt

胶条砂面接 Tape on gain	
胶条背面接 Tape on Backing	
搭接 Overlap	



砂纸产品 PAPER ABRASIVES

2025 E级重磅纸棕刚玉

磨料 Grain	棕刚玉 / Aluminium oxide	结合剂 Bonding	树脂 / Resin over Resin
基材 Backing	E级重磅纸 / E weight paper	植砂密度 Coating	半疏植砂 / Semi open
粒度范围 Grit range	P36~P400	处理 Treatment	抗静电 / Antistatic
大卷宽度 Jumbo width	1400mm / 1600mm	砂带宽度 Sanding belt width	最大 up to max 3300mm

产品特点 Application

- 磨削效率高，性价比好，使用范围广 / General purpes use, from disc to narrow belt, up to wide belt.



2027 E级重磅纸棕刚玉

磨料 Grain	精选棕刚玉 / Treated Alumina	结合剂 Bonding	树脂 / Resin over Resin
基材 Backing	E级重磅纸 / E weight paper	植砂密度 Coating	半疏植砂 / Semi open
粒度范围 Grit range	P36~P400	处理 Treatment	抗静电 / Antistatic
大卷宽度 Jumbo width	1400mm / 1600mm	砂带宽度 Sanding belt width	最大 up to max 3300mm

产品特点 Application

- 磨削锋利、效率高，寿命长，抗静电、不易堵塞 / High grinding performance, high effience, anti-logging, longer life time. Available from disc to narrow belt, up to wide belt.




2026 F级重磅纸棕刚玉

磨料 Grain	棕刚玉 / Aluminium oxide	结合剂 Bonding	树脂 / Resin over Resin
基材 Backing	F级重磅纸 / F weight paper	植砂密度 Coating	半疏植砂 / Semi open
粒度范围 Grit range	P36~P400	处理 Treatment	抗静电 / Antistatic
大卷宽度 Jumbo width	1400mm / 1600mm	砂带宽度 Sanding belt width	最大 up to max 3300mm

产品特点 Application

- 磨削锋利、效率高，抗静电、不易堵塞 / Sharp, strong paper backing, anti-clogging, good life, general purpes use, Available from disc to narrow belt, up to wide belt.



砂纸产品 PAPER ABRASIVES

1026 F级重磅纸碳化硅

磨料 Grain	碳化硅 / Silicon Carbide	结合剂 Bonding	树脂 / Resin over Resin
基材 Backing	F级重磅纸 / F-weight paper	植砂密度 Coating	半疏植砂 / Semi open
粒度范围 Grit range	P36~P400	处理 Treatment	抗静电 / Antistatic
大卷宽度 Jumbo width	1400mm / 1600mm	砂带宽度 Sanding belt width	最大 up to max 3300mm

- 磨削效率高，性价比好，使用范围广，用于家具、皮革、实木地板抛光 / General purpes use, from woodworking to leather, floor sanding etc. Available from disc to narrow belt, up to segmented wide belt.




1028 G级重磅纸碳化硅

NEW

磨料 Grain	碳化硅 / Silicon Carbide	结合剂 Bonding	树脂 / Resin over Resin
基材 Backing	G级重磅纸 / G-weight paper	植砂密度 Coating	半疏植砂 / Semi open
粒度范围 Grit range	P36~P400	处理 Treatment	抗静电 / Antistatic
大卷宽度 Jumbo width	1400mm / 1600mm	砂带宽度 Sanding belt width	最大 up to max 3300mm

- 适合于宽幅材料的连续抛光，平整性好，效率高，强度高适用于大型设备，可替代纸布混合 / Heavy duty, strong backing, suitable for large panel sander, a replacement for combination. Available from disc to narrow belt, up to segmented wide belt.



**碳化硅砂布产品 CLOTH ABRASIVES**

**1124 X级聚酯布碳化硅**

磨料 Grain	碳化硅 / Silicon Carbide	结合剂 Bonding	树脂 / Resin over Resin
基材 Backing	X级聚酯布 / X weight polyester	植砂密度 Coating	密植砂 / Close Coated
粒度范围 Grit range	P24~P240		
大卷宽度 Jumbo width	1400mm	砂带宽度 Sanding belt width	最大 up to max 1380mm



**产品特点 Application**  
 • 背基硬挺度适中, 适用范围广, 性价比高。适用于胶合板、中低密度板、一般打磨等 / Tough polyester backing for pressure sanding, good grinding, for plywood, MDF etc. Available from roll, disc to narrow belt, up to wide belt.



**1125 XY级聚酯布碳化硅**

磨料 Grain	碳化硅 / Silicon Carbide	结合剂 Bonding	树脂 / Resin over Resin
基材 Backing	XY级纯聚酯布 / XY weight polyester	植砂密度 Coating	密植砂 / Close Coated
粒度范围 Grit range	P24~P240		
大卷宽度 Jumbo width	1400mm	砂带宽度 Sanding belt width	最大 up to max 1380mm




**产品特点 Application**  
 • 背基硬挺度适中, 适用范围广, 磨削效率高、性价比高。适用于胶合板、中低密度板、玻璃、一般金属打磨等 / Tear-resistant and stiff polyester backing for high sanding pressure, good grinding, for board sanding, glass sanding etc. Available from roll, disc to narrow belt, up to wide belt.



**碳化硅砂布产品 CLOTH ABRASIVES**

**1126 Y级聚酯布碳化硅**

磨料 Grain	碳化硅 / Silicon Carbide	结合剂 Bonding	树脂 / Resin over Resin
基材 Backing	Y级纯聚酯布 / Y weight polyester	植砂密度 Coating	密植砂 / Close Coated
粒度范围 Grit range	P12~P240	处理 Treatment	抗静电 / Antistatic
大卷宽度 Jumbo width	1400mm	砂带宽度 Sanding belt width	最大 up to max 1380mm



**产品特点 Application**  
 • 布基硬挺, 适用范围广, 寿命好, 适用于刨花板、中高密度板、铝合金、玻璃、陶瓷、橡胶等 / Standard durable waterproof polyester abrasive, efficient grinding, can be widely use on MDF/HDF, OSB board sanding, and glass sanding, etc. Available from roll, disc to narrow belt, up to wide belt.



**1127 重Y级聚酯布碳化硅**

磨料 Grain	精选碳化硅 / Premium Silicon Carbide	结合剂 Bonding	树脂 / Resin over Resin
基材 Backing	重Y级纯聚酯布 / Heavy Y weight polyester	植砂密度 Coating	密植砂 / Close Coated
粒度范围 Grit range	P24~P240	处理 Treatment	抗静电 / Antistatic
大卷宽度 Jumbo width	1400mm	砂带宽度 Sanding belt width	最大 up to max 1380mm



**产品特点 Application**  
 • 厚重型聚酯布基, 硬挺度高, 抗冲击力好, 寿命长。适用于中高密度板、刨花板, 铝合金、大理石等 / Highly tear-resistant and stiff polyester backing for high sanding pressure, can be used in high humidity climatic conditions, for MDF/HDF, OSB and particle board sanding, glass, marble stone, alloy sanding etc. Available from roll, disc to narrow belt, up to wide belt.



砂布产品 CLOTH ABRASIVES

2112 X级聚酯布棕刚玉

磨料 Grain	棕刚玉 / Aluminium oxide	结合剂 Bonding	树脂 / Resin over Resin
基材 Backing	X级聚酯布 / X weight polyester	植砂密度 Coating	密植砂 / Close Coated
粒度范围 Grit range	P24~P600		
大卷宽度 Jumbo width	1400mm	砂带宽度 Sanding belt width	最大 up to max 1380mm

产品特点 Application

- 适合宽砂带以及窄砂带制作, 适用范围广, 性价比高, 用于胶合板、木材、普通金属 / General purposes use, from woodworking to metal sanding etc. Available from roll to narrow belt, up to wide belt.




2114 X级聚酯布棕刚玉

磨料 Grain	棕刚玉 / Aluminium oxide	结合剂 Bonding	树脂 / Resin over Resin
基材 Backing	X级聚酯布 / X weight polyester	植砂密度 Coating	密植砂 / Close Coated
粒度范围 Grit range	P24~P400		
大卷宽度 Jumbo width	1400mm	砂带宽度 Sanding belt width	最大 up to max 1380mm

产品特点 Application

- 砂面黑色, 适合宽砂带以及窄砂带制作, 适用范围广, 性价比高, 用于胶合板木材、普通打磨 / Alumina coated black, for general purposes, plywood sanding etc. Available from roll to narrow belt, up to wide belt.



3126 Y级聚酯布锆刚玉

磨料 Grain	锆刚玉 / Zirconia	结合剂 Bonding	树脂 / Resin over Resin
基材 Backing	重Y级纯聚酯布 / Heavy Y weight polyester	植砂密度 Coating	密植砂 / Close Coated
粒度范围 Grit range	P24~P120	处理 Treatment	抗静电 / Antistatic
大卷宽度 Jumbo width	1400mm	砂带宽度 Sanding belt width	最大 up to max 1380mm

产品特点 Application

- 尤其适用于有回收粉的板材粗磨, 脱砂少, 寿命长, 用于木材、普通金属、实木地板打磨, 防火板、防潮板的粗中细定厚及抛光 / Durable waterproof heavy duty backing, suitable for panel sander, specially working well with dust recycle process, also suitable for steel grinding, floor sanding etc. Available from roll, disc to narrow belt, up to wide belt.



碳化硅砂布产品 CLOTH ABRASIVES

1128 重YY级聚酯布碳化硅

超宽带 Segmented Belt

磨料 Grain	碳化硅 / Silicon Carbide	结合剂 Bonding	树脂 / Resin over Resin
基材 Backing	YY级纯聚酯布 / YY weight polyester	植砂密度 Coating	密植砂 / Close Coated
粒度范围 Grit range	P24~P220	处理 Treatment	抗静电 / Antistatic
大卷宽度 Jumbo width	1400mm / 1600mm	砂带宽度 Sanding belt width	最大 up to max 3300mm



**产品特点 Application**  
 ● 基体硬挺度高，平整型好，纬向延伸率小，寿命好。适用于超宽砂带制作，中高密度板、刨花板、不锈钢板、橡胶板的粗中细定厚及抛光 / Made with durable, tear-resistant polyester cloth backing for high sanding pressure, good life time at the same time efficient grinding, use for board/panel sanding, glass sanding etc. Available from roll to narrow belt, up to segmented wide belt.



1129 重YY级聚酯布碳化硅

超宽带 Segmented Belt

磨料 Grain	精选碳化硅 / Premium Silicon Carbide	结合剂 Bonding	树脂 / Resin over Resin
基材 Backing	YY级纯聚酯布 / YY weight polyester	植砂密度 Coating	密植砂 / Close Coated
粒度范围 Grit range	P24~P220	处理 Treatment	抗静电 / Antistatic
大卷宽度 Jumbo width	1600mm	砂带宽度 Sanding belt width	最大 up to max 3300mm



**产品特点 Application**  
 ● 基体硬挺度高，抗冲击性好，平整型好，寿命长。适用于超宽砂带制作，中高密度板、刨花板、不锈钢板、橡胶板的粗中细定厚及抛光 / Highly tear-resistant and stiff polyester backing for high sanding pressure, efficient grinding and long life time, can be widely use on board/panel sanding, glass sanding etc. Available from roll, disc to narrow belt, up to segmented wide belt.



采用德国标准化的砂带拨接技术，转接超宽砂带。最大宽度可达3300mm  
 Segmented belts can be made maximum width up to 3300mm

砂布产品 CLOTH ABRASIVES

3128 重YY级聚酯布锆刚玉

超宽带 Segmented Belt

磨料 Grain	锆刚玉 / Zirconia	结合剂 Bonding	树脂 / Resin over Resin
基材 Backing	YY级纯聚酯布 / YY weight polyester	植砂密度 Coating	密植砂 / Close Coated
粒度范围 Grit range	P40~P120	处理 Treatment	抗静电 / Antistatic
大卷宽度 Jumbo width	1580mm	砂带宽度 Sanding belt width	最大 up to max 3300mm



**产品特点 Application**  
 ● 尤其适用于有回收粉的板材粗磨，脱砂少，寿命长，用于中高密度板粗磨（多方向）刨花板、防火板、防潮板的粗中细定厚及抛光 / Highly tear-resistant and stiff polyester backing, suitable for panel sander, specially working well with dust recycle process, also suitable for steel grinding. Available from roll, disc to narrow belt, up to segmented wide belt.





金属材料表面处理 ABRASIVE FOR METAL SURFACE

1112 XY级聚酯布碳化硅

磨料 Grain	碳化硅 / Silicon Carbide	结合剂 Bonding	树脂 / Resin over Resin
基材 Backing	XY级纯聚酯布 / XY weight polyester	植砂密度 Coating	密植砂 / Close Coated
粒度范围 Grit range	P24~P400	处理 Treatment	防静电 / Antistatic
大卷宽度 Jumbo width	1400mm	砂带宽度 Sanding belt width	最大 up to max 1380mm

**产品特点 Application**

- 基体强度高，耐水耐油，性价比高，用于不锈钢拉丝，一般金属、实木、铝合金 / Tear-resistant and stiff polyester backing works well with oil or water, use on stainless steel surface sanding, general metal sanding, hard wood, alloys etc. Available from roll to narrow belt, up to wide belt.



1113 Y级聚酯布碳化硅

磨料 Grain	碳化硅 / Silicon Carbide	结合剂 Bonding	树脂 / Resin over Resin
基材 Backing	Y级纯聚酯布 / Y weight polyester	植砂密度 Coating	密植砂 / Close Coated
粒度范围 Grit range	P24~P400	处理 Treatment	防静电 / Antistatic
大卷宽度 Jumbo width	1650mm	砂带宽度 Sanding belt width	最大 up to max 3300mm

**产品特点 Application**

- 适用于超宽砂带制作，基体强度较高，耐水耐油，挺度高，用于不锈钢拉丝，一般金属、铝合金、不锈钢抛光 / Highly tear-resistant and stiff polyester backing for high sanding pressure, use on stainless steel surface sanding, general metal sanding, hard wood, alloys etc. Available from roll to narrow belt, up to segmented wide belt.



6708 Z级重聚酯布陶瓷刚玉

**NEW**

磨料 Grain	陶瓷刚玉 / Ceramic Alumina	结合剂 Bonding	树脂 / Resin over Resin
基材 Backing	Z级重纯聚酯布 / Z weight polyester	植砂密度 Coating	密植砂 / Close Coated
粒度范围 Grit range	P24~P120	处理 Treatment	超涂层 / Super coating
大卷宽度 Jumbo width	1400mm	砂带宽度 Sanding belt width	最大 up to max 1380mm

**产品特点 Application**

- 陶瓷刚玉 磨削锋利、效率高，用于钛合金、高碳铬不锈钢、硬质合金等的金属打磨 / Very highly tear-resistant and stiff polyester backing, highly efficient in metal grinding, long life time, super coating is also applied, suitable for titanium, hard alloys, carbon, cast iron, inconel, steel etc. Available from roll to narrow belt, up to wide belt.



硬金属打磨 ZIRCONIA ALUMINA FOR METAL

3516 Z级重聚酯布锆刚玉

**NEW**

磨料 Grain	锆刚玉 / Zirconia Alumina	结合剂 Bonding	树脂 / Resin over Resin
基材 Backing	Z级重纯聚酯布 / Z weight polyester	植砂密度 Coating	密植砂 / Close Coated
粒度范围 Grit range	P24~P120	处理 Treatment	无涂层 / non- top coating
大卷宽度 Jumbo width	1400mm	砂带宽度 Sanding belt width	最大 up to max 1380mm

**产品特点 Application**

- 抗冲击性好，寿命长，用于铸铁、不锈钢板、硬木板磨削、实木地板的粗磨 / Very highly tear-resistant and stiff polyester backing for high pressure grinding, for steel grinding, alloys, hard wood, floor sanding etc. Available from roll to narrow belt, up to wide belt.



3527 Z级重聚酯布涂层锆刚玉

**NEW**

磨料 Grain	锆刚玉 / Zirconia Alumina	结合剂 Bonding	树脂 / Resin over Resin
基材 Backing	Z级重纯聚酯布 / Z weight polyester	植砂密度 Coating	密植砂 / Close Coated
粒度范围 Grit range	P24~P120	处理 Treatment	超涂层 / Super coating
大卷宽度 Jumbo width	1400mm	砂带宽度 Sanding belt width	最大 up to max 1380mm

**产品特点 Application**

- 磨削接触面积小、磨削压强大的不锈钢工件，磨削锋利、效率高，用于钛合金、硬质合金、高碳铬不锈钢、耐热合金钢、灰铸铁、硬青铜等的粗磨、去毛刺和倒角 / Very highly tear-resistant and stiff polyester backing, efficient in metal grinding, special super coating for anti-clogging and heat resistant, works well at narrow belt, idea for titanium, alloys, carbon, cast iron, inconel, steel, forged steel, and stainless steel etc. Available from roll to narrow belt, up to wide belt.v




3538 Z级重聚酯布涂层锆刚玉 +

**NEW**

磨料 Grain	锆刚玉+ / Zirconia Alumina+	结合剂 Bonding	树脂 / Resin over Resin
基材 Backing	Z级重纯聚酯布 / Z weight polyester	植砂密度 Coating	密植砂 / Close Coated
粒度范围 Grit range	P24~P120	处理 Treatment	超涂层 / Super coating
大卷宽度 Jumbo width	1400mm	砂带宽度 Sanding belt width	最大 up to max 1380mm

**产品特点 Application**

- 磨削接触面积大、磨削压力大的不锈钢工件，磨削锋利、效率高，用于钛合金、高碳铬不锈钢、灰铸铁、硬青铜等的粗磨、去毛刺和倒角 / Very highly tear-resistant and stiff polyester backing, highly efficient in metal grinding, super coating for anti-clogging and heat resistant, works well at narrow belt, for titanium, alloys, carbon, cast iron, inconel, steel, forged steel, and stainless steel etc. Available from roll to narrow belt, up to wide belt.



钢纸基产品 VULCANIZED FIBER

1216 0.8钢纸碳化硅

磨料 Grain	碳化硅 / Silicon Carbide	结合剂 Bonding	树脂 / Resin over Resin
基材 Backing	0.8mm 钢纸 / 0.8mm Fiber	植砂密度 Coating	密植砂 / Close Coated
粒度范围 Grit range	P16~P120		
大卷宽度 Jumbo width	1600mm		

产品特点 Application

- 性价比高、磨削锋利, 用于大理石、陶瓷、玻璃钢的倒角打磨 / Eco-fiber abrasive, sharp, good life time. suitable for stone, ceramic, glass etc. Available from jumbo roll to disc



2216 0.8钢纸棕刚玉

磨料 Grain	棕刚玉 / Aluminium oxide	结合剂 Bonding	树脂 / Resin over Resin
基材 Backing	0.8mm 钢纸 / 0.8mm Fiber	植砂密度 Coating	密植砂 / Close Coated
粒度范围 Grit range	P16~P120		
大卷宽度 Jumbo width	1600mm		

产品特点 Application

- 使用范围广、性价比高, 适用于普通金属、实木家具的除锈、去毛刺和倒角打磨 / General fiber backing abrasive, good life time, suitable for general metal, hard wood, rusty removal etc. Available from jumbo roll to disc



2217 0.8钢纸煅烧氧化铝

磨料 Grain	煅烧氧化铝 / Fused Alumina	结合剂 Bonding	树脂 / Resin over Resin
基材 Backing	0.8mm 钢纸 / 0.8mm Fiber	植砂密度 Coating	密植砂 / Close Coated
粒度范围 Grit range	P24~P120		
大卷宽度 Jumbo width	1600mm		

产品特点 Application

- 磨削效率高, 寿命长。适用于金属焊接位、去毛刺和倒角打磨 / Sharp and efficient grinding, long life time, suitable for welding sanding, rusty removal etc. Available from jumbo roll to disc



3216 0.8钢纸锆刚玉

磨料 Grain	锆刚玉 / Zirconia Alumina	结合剂 Bonding	树脂 / Resin over Resin
基材 Backing	0.8mm 钢纸 / 0.8mm Fiber	植砂密度 Coating	密植砂 / Close Coated
粒度范围 Grit range	P24~P120		
大卷宽度 Jumbo width	1600mm		

产品特点 Application

- 磨削效率高、抗冲击性强, 寿命长。适用于铝合金、不锈钢, 金属、大理石, 红木家具的除锈、焊接位、去毛刺和倒角打磨 / Sharp and highly efficient grinding, resistant to high pressure, long life time, suitable for alloys, stainless steel, steel, welding sanding, rusty removal etc. Available from jumbo roll to disc



938 石墨布卷 GRAPHITE COATED CANVAS HD

HD 重型负载石墨布具有良好抗压、抗热性能, 是配合砂带、砂光设备一起使用的最佳选择

Heavy duty graphite coated canvas for the use in applications of high heat and pressure composite panel sanding



927 羊毛毡 WOOL FELT

WEEM 927 羊毛毡采用100%纯羊毛, 是最佳的垫板材料

Use 100% pure wool, perfect support for sanding pad covers.

厚度 Thickness 3mm \ 4mm \ 5mm

密度 Density 0.36~0.44 g/ccm



# WEEM ABRASIVES

韶关威鸣研磨材料有限公司

地址：广东省韶关市乳源县乳城镇迎宾路富源大道南侧，512700

WEEM Abrasives(Shaoguan) Co., Ltd

Add: No.12 Fuyuan Industrial Area, Yingbin Road, Ruyuan town, Guangdong, China.